

# CRV 6000A

## 5,6" LCD Monitor with Color Camera



### Besonderheiten

#### 5,6" TFT LCD Farb Monitor

- Auflösung 960(H) x 234(V)
- Integrierter Lautsprecher mit Lautstärkeregelung
- 2 Kamera Eingänge (CA1, CA2) umschaltbar (AXION 4 Pin mini DIN Buchsen)
- Video System NTSC/PAL (automatisch)
- Spiegel oder Normalbildfunktion
- Manuelle oder automatische Einschaltmöglichkeit sobald Rückwärtsgang eingelegt wird (CA1)
- Farb & Helligkeitseinstellung
- Tag / Nacht Umschaltung
- A/V Eingang & Ausgang
- Erschütterungsbeständig
- Stromversorgung 10V – 32V DC
- Leistungsbedarf max. 8,4 W
- Gewicht 0,52 Kg
- Abmessungen (BxHxT): 174x125x46mm

#### 1/3" CCD Farb Kamera

- LED'S zur gleichmäßigen Ausleuchtung bei Dunkelheit
- Hohe Lichtempfindlichkeit (0,5 Lux)
- Elektronischer Helligkeitsabgleich
- Automatische elektronische Blende
- Großer Blickwinkel (Diagonal 130°)
- Wasserdichtes Mikrofon
- Widerstandsfähig gegen Vandalismus & Feuchtigkeit (IP67)
- Stromversorgung 12V DC (vom Monitor)
- Wetterfestes Aluminium-Druckguss-Gehäuse mit Sonnenblende / Befestigungsbügel & Schrauben
- 20 m Verbindungskabel (mit wasserdichtem WPC Stecker)
- Abmessungen (BxHxT): 68 x 41 x 59 mm

### Features

#### 5,6" TFT LCM color monitor


- Resolution 960(H) x 234(V)
- Integrated loudspeaker with volume control
- 2 camera inputs (CA1, CA2) switch- able (AXION 4 Pin mini DIN jack)
- Video system NTSC/PAL (automatic)
- Mirror or normal picture function
- Manual or automatic picture display whenever reverse gear is engaged (CA1)
- Color & brightness adjustment
- Day / night switch
- A/V input & output
- Shock resistant
- Power supply: 10V – 32V DC
- Power consumption max. 8,4 W
- Weight 0,52 Kg
- Measures (WxHxD): 174x125x46mm

#### 1/3" CCD color camera

- LED'S for even illumination in darkness
- Strong light-sensitiveness (0,5 Lux)
- Electronic lightness adjustment
- Automatic electronic iris
- Large viewing angel (diagonal 130°)
- Waterproof microphone
- Vandal resistant & waterproof (IP67)
- Power supply 12V DC (of the monitor)
- Weatherproof Al. die-cast case with sun-shield / mounting bracket & screws
- 20 m connecting cable (with waterproof WPC connector)
- Measures (WxHxD): 68 x 41 x 59 mm

EAN Code: 4041044220633

## Technical data:

Camera	CRV 6000	Monitor	CRV 6000
Color system	Color	B/W / Color	Color
Image device	1/3" CCD Image Sensor	Video system	PAL / NTSC
Picture elements	320.000 (PAL)	Display size	5,6"
Resolution lines	380 TV lines	Deflection angel	65°
Electronic shutter	Built in	Resolution	960 (H) x 234 (V)
Black light comp.	Built in	vibration resistance	5,5 G
AGC/flicker less	Built in	Loudspeaker	0,5W (8 Ohm)
Angel of view (focal width)	Diagonal 130° (F=2)	Power connector	Red: positive 10V to 32 V DC
Illumination	< 0,5 Lux		Green: Reverse gear 12V to 24 V DC
S/N ratio	47 dB		Black: Ground
Waterproof	yes	Input	4 PIN mini DIN
Mirror	yes		1 Power DC 12 V
Audio output	yes		2 Audio Input
Operating temp.	-30°C to +50°C		3 Nor / Mir
Dimension (WxHxD)	68x41x59 mm		4 Video Input
Power consumption	max. 2 W		5 Ground
Housing	Aluminium	Power consumption	< 6W
Power input	12 V DC	Operating Temperatur Range	-30°C to +60°C
Weight	0.480 Kg	Storage Temperature Range	-40 to +85°C
Vibrations resistant	6 G	Dimension (WxHxD)	174x125x46 mm
protection category	IP 67	Weight	0,520 Kg